

SAFETY DATA SHEET

Sikadur-52 (IN) SLV, Component B



Revision Date 24.09.2018

Print Date 24.09.2018

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikadur-52 (IN) SLV, Component B
Product code : 100000022664
Type of product : liquid

Manufacturer or supplier's details

Company : Sika India Private Ltd.
Unit 501-502, B- Wing, 5th floor
Lotus Corporate Park
Off Western Express Highway
Goregaon East
Mumbai 400 063
Telephone : +9122 6270 4038
E-mail address : ehs.india@in.sika.com
Emergency telephone number : +9122 6270 4038

2. HAZARDS IDENTIFICATION

Manufacture, Storage and Import of Hazardous Chemicals Rules 1989

Classification

Flammable liquid

GHS Classification

Flammable liquids : Category 4
Acute toxicity (Oral) : Category 4
Acute toxicity (Inhalation) : Category 4
Skin corrosion/irritation : Sub-category 1A
Serious eye damage/eye irritation : Category 1
Skin sensitisation : Category 1
Short-term (acute) aquatic hazard : Category 3

GHS label elements

Hazard pictograms :

Signal word : Danger

Hazard statements : H227 Combustible liquid.

SAFETY DATA SHEET

Sikadur-52 (IN) SLV, Component B



Revision Date 24.09.2018

Print Date 24.09.2018

H302 + H332 Harmful if swallowed or if inhaled.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H402 Harmful to aquatic life.

Precautionary statements

: **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 Store in a well-ventilated place.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration (%)
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	25513-64-8	>= 50 - < 70
Polyoxypropylenediamine	9046-10-0	>= 10 - < 20
Cashew, nutshell liq.	8007-24-7	>= 10 - < 20
Amines, polyethylenepoly-, triethylenetetramine	90640-67-8	>= 5 - < 10

SAFETY DATA SHEET

Sikadur-52 (IN) SLV, Component B



Revision Date 24.09.2018

Print Date 24.09.2018

fraction		
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	$\geq 3 - < 5$
2,2'-iminodiethylamine	111-40-0	$\geq 3 - < 5$
p-toluenesulphonic acid (containing a maximum of 5 % H ₂ SO ₄)	104-15-4	$\geq 1 - < 10$

4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Health injuries may be delayed.
corrosive effects
sensitising effects
Gastrointestinal discomfort
Respiratory disorder
Allergic reactions
Headache
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
Harmful if swallowed or if inhaled.
May cause an allergic skin reaction.
Causes serious eye damage.
Causes severe burns.
- Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO₂)

SAFETY DATA SHEET

Sikadur-52 (IN) SLV, Component B



Revision Date 24.09.2018

Print Date 24.09.2018

- Unsuitable extinguishing media : Water
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Follow standard hygiene measures when handling chemical products
- Conditions for safe storage : Store in original container.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.

SAFETY DATA SHEET

Sikadur-52 (IN) SLV, Component B



Revision Date 24.09.2018

Print Date 24.09.2018

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2,2'-iminodiethylamine	111-40-0	TWA	1 ppm	ACGIH

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : amber
- Odour : amine-like
- Odour Threshold : No data available
- pH : No data available
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : 61 °C (142 °F)
Method: closed cup

SAFETY DATA SHEET

Sikadur-52 (IN) SLV, Component B



Revision Date 24.09.2018

Print Date 24.09.2018

Evaporation rate	: No data available
Flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 0.04 hPa (0.03 mmHg)
Relative vapour density	: No data available
Density	: 0.95 g/cm ³ (20 °C (68 °F) ())
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 20.5 mm ² /s (40 °C)
Explosive properties	: No data available
Molecular weight	: No data available

10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: No data available
Incompatible materials	: No data available
No decomposition if stored and applied as directed.	

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed or if inhaled.

SAFETY DATA SHEET

Sikadur-52 (IN) SLV, Component B



Revision Date 24.09.2018

Print Date 24.09.2018

Components:

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine:

Acute oral toxicity : LD50 Oral (Rat): 910 mg/kg

Cashew, nutshell liq.:

Acute oral toxicity : LD50 Oral (Rat): 500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 2,000 mg/kg

Amines, polyethylenepoly-, triethylenetetramine fraction:

Acute oral toxicity : LD50 Oral (Rat): 1,716 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,465 mg/kg

2,4,6-tris(dimethylaminomethyl)phenol:

Acute oral toxicity : LD50 Oral (Rat): 2,169 mg/kg

2,2'-iminodiethylamine:

Acute oral toxicity : LD50 Oral (Rat): 1,553 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.071 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): 1,045 mg/kg

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

Sikadur-52 (IN) SLV, Component B



Revision Date 24.09.2018

Print Date 24.09.2018

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine:

Toxicity to algae : EC50 (Scenedesmus capricornutum (fresh water algae)): 29.5 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : LC50 (Leuciscus idus (Golden orfe)): 174 mg/l
Exposure time: 48 h

Polyoxypropylenediamine:

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (algae)): 15 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50 (Daphnia magna (Water flea)): 80 mg/l
Exposure time: 48 h

2,4,6-tris(dimethylaminomethyl)phenol:

Toxicity to algae : EC50 (Scenedesmus capricornutum (fresh water algae)): > 10 - 100 mg/l
Exposure time: 72 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SAFETY DATA SHEET

Sikadur-52 (IN) SLV, Component B



Revision Date 24.09.2018

Print Date 24.09.2018

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine)
Class : 9
Packing group : III
Labels : 9

IATA-DGR

UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine)
Class : 9
Packing group : III
Labels : 9
Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964

IMDG-Code

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine)
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

16. OTHER INFORMATION

Date format : dd.mm.yyyy

SAFETY DATA SHEET

Sikadur-52 (IN) SLV, Component B



Revision Date 24.09.2018

Print Date 24.09.2018

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.