Sikadur-32 LP, Component A

Revision Date 30.07.2017



1. PRODUCT AND COMPANY IDENTIFICATION

Product name	: Sikadur-32 LP, Component A					
Product code	: 000000612210					
Type of product	: liquid					
Manufacturer or supplier's details						
Company	 Sika India Private Ltd. Unit 501-502, B- Wing, 5th floor Lotus Corporate Park Off Western Express Highway Goregaon East Mumbai 400 063 					
Telephone	: +9122 6270 4038					
E-mail address	: ehs.india@in.sika.com					
Emergency telephone num- ber	: +9122 6270 4038					

2. HAZARDS IDENTIFICATION

Manufacture, Storage and Import of Hazardous Chemicals Rules 1989

Classification	
Flammable liquid	
GHS Classification	
Flammable liquids	: Category 4
Skin corrosion/irritation	: Category 2
Serious eye damage/eye irri- tation	: Category 2A
Skin sensitisation	: Category 1
Chronic aquatic toxicity	: Category 2
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: H227 Combustible liquid. H315 Causes skin irritation.

Sikadur-32 LP, Component A

Revision Date 30.07.2017



	H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements :	 Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P302 + P352 IF ON SKIN: Wash with plenty of water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. P31 Collect spillage. Storage: P403 Store in a well-ventilated place. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration (%)
barium sulfate	7727-43-7	>= 50 - < 70
reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700)		>= 30 - < 50
oxirane, mono[(C12-14-alkyloxy)methyl]derivs	68609-97-2	>= 1 - < 10

4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air.

Sikadur-32 LP, Component A

Revision Date 30.07.2017



	Consult a physician after significant exposure.
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	 Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	 Clean mouth with water and drink afterwards plenty of water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.
Most important symptoms and effects, both acute and delayed	 irritant effects sensitising effects Allergic reactions Excessive lachrymation Dermatitis See Section 11 for more detailed information on health effects and symptoms. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.
Notes to physician	: Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Carbon dioxide (CO2)
Unsuitable extinguishing media	: Water
Specific hazards during fire- fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	: No hazardous combustion products are known
Specific extinguishing meth- ods	 Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec-	: Use personal protective equipment.
tive equipment and emer-	Deny access to unprotected persons.
gency procedures	

Sikadur-32 LP, Component A

Revision Date 30.07.2017



Environmental precautions	:	: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.	
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.	
7. HANDLING AND STORAGE			
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.	
Advice on safe handling	:	Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the ap- plication area. Follow standard hygiene measures when handling chemical products	
Conditions for safe storage	:	Store in original container. Keep in a well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in accordance with local regulations.	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Personal protective equipment

r croonar proteotive equipi	
Respiratory protection	: Use respiratory protection unless adequate local exhaust ven- tilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max- imum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.
Hand protection	: Chemical-resistant, impervious gloves complying with an ap- proved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

Sikadur-32 LP, Component A

Revision Date 30.07.2017



		essary.
Eye protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	:	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	viscous liquid
Colour	:	off-white
Odour	:	odourless
Odour Threshold	:	No data available
рН	:	No data available
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	62 °C (144 °F) Method: closed cup
Evaporation rate	:	No data available
Flammability	:	No data available
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	0.01 hPa (0.01 mmHg)
Relative vapour density	:	No data available
Density	:	1.7 g/cm3 (20 °C (68 °F) ())
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available

Sikadur-32 LP, Component A

Revision Date 30.07.2017



Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity Viscosity, dynamic	: > 2,000 mPa.s (30 °C)
Viscosity, kinematic	: > 20.5 mm2/s (40 °C)
Explosive properties	: No data available
Molecular weight	: No data available

10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reac- tions	: Stable under recommended storage conditions.
Conditions to avoid	: No data available
Incompatible materials	: No data available
No decomposition if stored and applied as directed.	

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

reaction product: bispheno lar weight <= 700):	I-A-(epichlorhydrin) and epoxy resin (number average molecu-
Acute oral toxicity	: LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction. Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Sikadur-32 LP, Component A

Revision Date 30.07.2017

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:			
reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecu-			
lar weight <= 700):			
Toxicity to fish	60 (Oncorhynchus mykiss (rair osure time: 96 h	nbow trout)): 2 mg/l	
Toxicity to daphnia and other aquatic invertebrates	50 (Daphnia magna (Water fle osure time: 48 h	a)): 1.8 mg/l	
Persistence and degradability			
No data available			
Bioaccumulative potential			
No data available			
Mobility in soil			
No data available			
Other adverse effects			
Product:			
Additional ecological infor- mation	ic to aquatic life with long last	ng effects.	

13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemi- cal or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.



Sikadur-32 LP, Component A

Revision Date 30.07.2017



Do not burn, or use a cutting torch on, the empty drum.

14. TRANSPORT INFORMATION

International Regulations		
UNRTDG UN number Proper shipping name	 : UN 3082 : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. 	
Class	: 9	
Packing group Labels	: III : 9	
IATA-DGR UN/ID No. Proper shipping name Class Packing group Labels Packing instruction (cargo aircraft) Packing instruction (passen- ger aircraft)	 UN 3082 Environmentally hazardous substance, liquid, n.o.s. 9 III 9 964 964 	
IMDG-Code UN number Proper shipping name	: UN 3082 : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	
Class Packing group Labels EmS Code Marine pollutant	: 9 : III : 9 : F-A, S-F : no	
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code		

Not applicable for product as supplied.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

16. OTHER INFORMATION

Date format

: dd.mm.yyyy

Sikadur-32 LP, Component A

Revision Date 30.07.2017



The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.