Sikadur®-42 MP (IN) Comp. A

Revision Date 12.04.2018



1. PRODUCT AND COMPANY IDENTIFICATION

Product name	:	Sikadur [®] -42 MP (IN) Comp. A
Product code	:	100000014224
Type of product	:	liquid
Manufacturer or supplier's c	deta	ils
Company	:	Sika India Private Ltd. Unit 501-502, B- Wing, 5th floor Lotus Corporate Park Off Western Express Highway Goregaon East Mumbai 400 063
Telephone	:	+9122 4038 4038
E-mail address	:	ehs.india@in.sika.com
Emergency telephone num- ber	:	+9122 4038 4038

2. HAZARDS IDENTIFICATION

Manufacture, Storage and Import of Hazardous Chemicals Rules 1989

Classification

Not classified as hazardous according to criteria laid down in Part I of Schedule-1.

GHS Classification	
Skin corrosion/irritation	: Category 2
Serious eye damage/eye irri- tation	: Category 2A
Skin sensitisation	: Category 1
Chronic aquatic toxicity	: Category 2
GHS label elements Hazard pictograms	
Signal word	: Warning
Hazard statements	 H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

Sikadur®-42 MP (IN) Comp. A

Revision Date 12.04.2018



	H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	 Prevention: P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/ eye protection/ face protection. Response: P302 + P352 IF ON SKIN: Wash with plenty of water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration (%)
	25068-38-6	>= 90 - <= 100
epoxy resin (number average molecular weight <=		
700)		
oxirane, mono[(C12-14-alkyloxy)methyl]derivs	68609-97-2	>= 1 - < 10
Hydrocarbons, C10-C13, aromatic, >1% Naphtha-	64742-94-5	>= 0.25 - < 1
lene		

4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance	÷.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.	
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician. 	
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses.	

Sikadur®-42 MP (IN) Comp. A

Print Date 12.04.2018

Revision Date 12.04.2018

	Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	 Clean mouth with water and drink afterwards plenty of water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.
Most important symptoms and effects, both acute and delayed	 irritant effects sensitising effects Allergic reactions Excessive lachrymation Dermatitis See Section 11 for more detailed information on health effects and symptoms. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.
Notes to physician	: Treat symptomatically.
5. FIREFIGHTING MEASURES	
Suitable extinguishing media	: Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.

Canadio oxingalonnig moala	•	cumstances and the surrounding environment.
Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
Specific extinguishing meth- ods	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	Use personal protective equipment. Deny access to unprotected persons.	
Environmental precautions	Do not flush into surface water or sanitary sewer system If the product contaminates rivers and lakes or drains int respective authorities.	
Methods and materials for containment and cleaning up	Soak up with inert absorbent material (e.g. sand, silica g acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.	∣el,

Sikadur®-42 MP (IN) Comp. A

Revision Date 12.04.2018



7. HANDLING AND STORAGE

Advice on protection against fire and explosion	: Normal measures for preventive fire protection.
Advice on safe handling	 Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
Conditions for safe storage	 Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Personal protective equipment

Respiratory protection	e respiratory protection unless adequa ation is provided or exposure assessme posures are within recommended expo e filter class for the respirator must be um expected contaminant concentration as/vapour/aerosol/particulates) that ma ng the product. If this concentration is e ntained breathing apparatus must be u	ent demonstrates that sure guidelines. suitable for the max- n y arise when han- exceeded, self-
Hand protection	nemical-resistant, impervious gloves co oved standard should be worn at all tim emical products if a risk assessment in sary.	ies when handling
Eye protection	fety eyewear complying with an approvulue used when a risk assessment indicate	
Skin and body protection	noose body protection in relation to its t tion and amount of dangerous substan ic work-place.	
Hygiene measures	andle in accordance with good industria actice. hen using do not eat or drink.	I hygiene and safety

Sikadur®-42 MP (IN) Comp. A

Revision Date 12.04.2018



When using do not smoke. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	viscous liquid
Colour	:	translucent
Odour	:	No data available
Odour Threshold	:	No data available
рН	:	No data available
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	> 101 °C (> 214 °F) Method: closed cup
Evaporation rate	:	No data available
Flammability	:	No data available
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	0.01 hPa (0.01 mmHg)
Relative vapour density	:	No data available
Density	:	ca. 1.1 g/cm3
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	> 600 mPa.s (30 °C)
Viscosity, kinematic	:	> 20.5 mm2/s (40 °C)

Print Date 12.04.2018

Sikadur®-42 MP (IN) Comp. A

Revision Date 12.04.2018

Explosive properties	: No data available
Molecular weight	: No data available

10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.			
Chemical stability	: The product is chemically stable.			
Possibility of hazardous reac- tions	: Stable under recommended storage conditions.			
Conditions to avoid	: No data available			
Incompatible materials	: No data available			
No decomposition if stored and applied as directed.				

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700): Acute oral toxicity

route oral toxiony	. ED00 Oral (Rat). > 0,000 mg/kg	

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction. Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Sikadur®-42 MP (IN) Comp. A

Revision Date 12.04.2018

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components: reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700): : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Toxicity to fish Exposure time: 96 h Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l aquatic invertebrates Exposure time: 48 h Persistence and degradability No data available **Bioaccumulative potential** No data available Mobility in soil No data available Other adverse effects Product: Additional ecological infor-: Toxic to aquatic life with long lasting effects. mation

13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemi- cal or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG		
UN number	:	UN 3082
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.



Sikadur®-42 MP (IN) Comp. A

Revision Date 12.04.2018



	epoxy resin)	
Class		
Packing group	l	
Labels		
IATA-DGR		
UN/ID No.	N 3082	
Proper shipping name	nvironmentally hazardous substance epoxy resin)	e, liquid, n.o.s.
Class		
Packing group	l	
Labels		
Packing instruction (cargo aircraft)	64	
Packing instruction (passen- ger aircraft)	64	
IMDG-Code		
UN number	N 3082	
Proper shipping name	NVIRONMENTALLY HAZARDOUS .O.S. epoxy resin)	SUBSTANCE, LIQUID,
Class		
Packing group	I	
Labels		
EmS Code	-A, S-F	
Marine pollutant	0	

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

16. OTHER INFORMATION

Date format

: dd.mm.yyyy

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.