

# SAFETY DATA SHEET

## Sikadur-52 (IN) SLV, Component A



Revision Date 24.09.2018

Print Date 24.09.2018

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikadur-52 (IN) SLV, Component A  
Product code : 100000022663  
Type of product : liquid

#### Manufacturer or supplier's details

Company : Sika India Private Ltd.  
Unit 501-502, B- Wing, 5th floor  
Lotus Corporate Park  
Off Western Express Highway  
Goregaon East  
Mumbai 400 063  
Telephone : +9122 6270 4038  
E-mail address : ehs.india@in.sika.com  
Emergency telephone number : +9122 6270 4038

### 2. HAZARDS IDENTIFICATION

#### Manufacture, Storage and Import of Hazardous Chemicals Rules 1989

##### Classification

Not classified as hazardous according to criteria laid down in Part I of Schedule-1.

##### GHS Classification

Skin corrosion/irritation : Category 2  
Skin sensitisation : Category 1  
Long-term (chronic) aquatic hazard : Category 2

##### GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.

# SAFETY DATA SHEET

## Sikadur-52 (IN) SLV, Component A



Revision Date 24.09.2018

Print Date 24.09.2018

P273 Avoid release to the environment.

P280 Wear protective gloves.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards which do not result in classification**

None known.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Hazardous components**

Chemical name	CAS-No.	Concentration (%)
reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	9003-36-5	>= 90 - <= 100
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	>= 1 - < 10

### 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects  
sensitising effects  
Allergic reactions  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.  
Causes skin irritation.

# SAFETY DATA SHEET

## Sikadur-52 (IN) SLV, Component A



Revision Date 24.09.2018

Print Date 24.09.2018

Notes to physician : May cause an allergic skin reaction.  
: Treat symptomatically.

---

### 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

---

### 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.

# SAFETY DATA SHEET

## Sikadur-52 (IN) SLV, Component A



Revision Date 24.09.2018

Print Date 24.09.2018

- Follow standard hygiene measures when handling chemical products
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Store in accordance with local regulations.

---

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

#### Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

---

### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : colourless
- Odour : odourless
- Odour Threshold : No data available
- pH : No data available

# SAFETY DATA SHEET

## Sikadur-52 (IN) SLV, Component A



Revision Date 24.09.2018

Print Date 24.09.2018

Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 101 °C (> 214 °F)
Evaporation rate	: No data available
Flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 0.01 hPa (0.01 mmHg)
Relative vapour density	: No data available
Density	: 1.02 g/cm <sup>3</sup> (20 °C (68 °F) ())
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 20.5 mm <sup>2</sup> /s (40 °C)
Explosive properties	: No data available
Molecular weight	: No data available

---

### 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: No data available
Incompatible materials	: No data available
No decomposition if stored and applied as directed.	

# SAFETY DATA SHEET

## Sikadur-52 (IN) SLV, Component A



Revision Date 24.09.2018

Print Date 24.09.2018

---

### 11. TOXICOLOGICAL INFORMATION

**Acute toxicity**

No data available

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Respiratory or skin sensitisation**

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

---

### 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

**Product:**

Additional ecological information : Toxic to aquatic life with long lasting effects.

---

### 13. DISPOSAL CONSIDERATIONS

**Disposal methods**

# SAFETY DATA SHEET

## Sikadur-52 (IN) SLV, Component A



Revision Date 24.09.2018

Print Date 24.09.2018

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

---

### 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

- UN number : UN 3082  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(epoxy resin)  
Class : 9  
Packing group : III  
Labels : 9

##### IATA-DGR

- UN/ID No. : UN 3082  
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.  
(epoxy resin)  
Class : 9  
Packing group : III  
Labels : 9  
Packing instruction (cargo aircraft) : 964  
Packing instruction (passenger aircraft) : 964

##### IMDG-Code

- UN number : UN 3082  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(epoxy resin)  
Class : 9  
Packing group : III  
Labels : 9  
EmS Code : F-A, S-F  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

---

### 15. REGULATORY INFORMATION

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

# SAFETY DATA SHEET

## Sikadur-52 (IN) SLV, Component A



Revision Date 24.09.2018

Print Date 24.09.2018

Schedules of Toxic Chemicals and Precursors

---

### 16. OTHER INFORMATION

Date format : dd.mm.yyyy

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.