Sikafloor®-161 HC Comp.A

Revision Date 29.03.2018



1. PRODUCT AND COMPANY IDENTIFICATION

Product name	:	Sikafloor [®] -161 HC Comp.A	
Product code	:	10000020391	
Type of product	:	liquid	
Manufacturer or supplier's details			
Company	:	Sika India Private Ltd. Unit 501-502, B- Wing, 5th floor Lotus Corporate Park Off Western Express Highway Goregaon East Mumbai 400 063	
Telephone	:	+9122 6270 4038	
E-mail address	:	ehs.india@in.sika.com	
Emergency telephone num- ber	:	+9122 6270 4038	

2. HAZARDS IDENTIFICATION

Manufacture, Storage and Import of Hazardous Chemicals Rules 1989

Classification

Not classified as hazardous according to criteria laid down in Part I of Schedule-1.

GHS Classification Skin corrosion/irritation	: Category 2
Skinconosion/initiation	
Serious eye damage/eye irri- tation	: Category 2A
Skin sensitisation	: Category 1
Chronic aquatic toxicity	: Category 2
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	 H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

Sikafloor®-161 HC Comp.A

Revision Date 29.03.2018



	H411 Toxic to aquatic life with long lasting effects.
Precautionary statements :	 Prevention: P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/ eye protection/ face protection. Response: P302 + P352 IF ON SKIN: Wash with plenty of water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration (%)
Quartz (SiO2)	14808-60-7	>= 50 - < 70
reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700)		>= 30 - < 50
oxirane, mono[(C12-14-alkyloxy)methyl]derivs	68609-97-2	>= 1 - < 10
benzyl alcohol	100-51-6	>= 1 - < 10

4. FIRST AID MEASURES

General advice		Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	•	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact		Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact		Immediately flush eye(s) with plenty of water. Remove contact lenses.

Sikafloor®-161 HC Comp.A



Revision Date 29.03.2018

5.

ucts

ods

for firefighters

	Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	 Clean mouth with water and drink afterwards plenty of water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.
Most important symptoms and effects, both acute and delayed	 irritant effects sensitising effects Allergic reactions Excessive lachrymation Dermatitis See Section 11 for more detailed information on health effects and symptoms. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.
Notes to physician	: Treat symptomatically.
FIREFIGHTING MEASURES	
Suitable extinguishing media	: Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Specific hazards during fire- fighting	: Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion prod- : No hazardous combustion products are known

: Collect contaminated fire extinguishing water separately. This

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

must not be discharged into drains.

6. ACCIDENTAL RELEASE MEASURES

Specific extinguishing meth-

Personal precautions, protec- tive equipment and emer- gency procedures	Use personal protective equipment. Deny access to unprotected persons.	
Environmental precautions	Do not flush into surface water or sanitary sewer system If the product contaminates rivers and lakes or drains in respective authorities.	
Methods and materials for containment and cleaning up	Soak up with inert absorbent material (e.g. sand, silica acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.	gel,

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Sikafloor®-161 HC Comp.A

Revision Date 29.03.2018



7. HANDLING AND STORAGE

Advice on protection against fire and explosion	: Normal measures for preventive fire protection.
Advice on safe handling	 Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
Conditions for safe storage	 Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ven- tilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max- imum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec- essary.
Eye protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	:	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink.

Sikafloor®-161 HC Comp.A

Revision Date 29.03.2018



When using do not smoke. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: grey
Odour	: very faint
Odour Threshold	: No data available
рН	: No data available
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 93.3 °C (> 199.9 °F) Method: closed cup
Evaporation rate	: No data available
Flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 0.001 hPa (0.001 mmHg)
Relative vapour density	: No data available
Density	: 1.6 g/cm3
Solubility(ies) Water solubility	: insoluble
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity Viscosity, dynamic	: 8,000 mPa.s (30 °C)
Viscosity, kinematic	: > 20.5 mm2/s (40 °C)
Explosive properties	: No data available

Sikafloor®-161 HC Comp.A



Revision Date 29.03.2018

Molecular weight

: No data available

10. STABILITY AND REACTIVITY		
Reactivity	: No dangerous reaction known under conditions of normal use.	
Chemical stability	: The product is chemically stable.	
Possibility of hazardous reac- tions	: Stable under recommended storage conditions.	
Conditions to avoid	: No data available	
Incompatible materials	: No data available	
No decomposition if stored and applied as directed.		

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecu- lar weight <= 700):		
Acute oral toxicity	: LD50 Oral (Rat): > 5,000 mg/kg	
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 20,000 mg/kg	
benzyl alcohol: Acute oral toxicity	: LD50 Oral (Rat): 1,620 mg/kg	
Acute inhalation toxicity	: LC50 (Rat): > 4.178 mg/l Exposure time: 4 h Test atmosphere: dust/mist	

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction. Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Sikafloor®-161 HC Comp.A



Revision Date 29.03.2018

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700): Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l aquatic invertebrates Exposure time: 48 h benzyl alcohol: Toxicity to fish : LC50 (Fish): > 100 mg/l Exposure time: 96 h Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l aquatic invertebrates Exposure time: 48 h Persistence and degradability No data available **Bioaccumulative potential** No data available Mobility in soil No data available Other adverse effects

Product:

Additional ecological infor- : Toxic to aquatic life with long lasting effects. mation

13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemi- cal or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product.

Sikafloor®-161 HC Comp.A

Revision Date 29.03.2018



Do not re-use empty containers.

14. TRANSPORT INFORMATION

International Regulations	
UNRTDG UN number	: UN 3082
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
Class	: 9
Packing group	: 111
Labels	: 9
IATA-DGR	
UN/ID No.	: UN 3082
Proper shipping name	 Environmentally hazardous substance, liquid, n.o.s. (epoxy resin)
Class	: 9
Packing group	: 111
Labels	: 9
Packing instruction (cargo aircraft)	: 964
Packing instruction (passen- ger aircraft)	: 964
IMDG-Code	
UN number	: UN 3082
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Class	(epoxy resin) : 9
Packing group	:
Labels	: 9
EmS Code	: F-A, S-F
Marine pollutant	: no
Transport in bulk apparding	to Annay II of MARRAI 72/79 and the IRC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

15. REGULATORY INFORMATION

Safety, he	ealth ar	nd environm	ental regu	lations	/legislatio	n specif	ic for	the substance	or mix-
ture									
			-						

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

16. OTHER INFORMATION

Date format

: dd.mm.yyyy

Sikafloor®-161 HC Comp.A

Revision Date 29.03.2018



The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.