

# Antisol® E

## Concrete curing compounds

Construction

<b>Product Description</b>	Paraffin dispersion based liquid curing compound without pigmented for concrete. Ready for use and simple to apply.
<b>Uses</b>	Antisol® E curing compound is sprayed on newly laid concrete surface to form a thin film barrier against premature water loss. Without disturbance to the normal setting action, the concrete is then allowed to cure and achieve maximum properties. Antisol® E is particularly useful in large areas of exposed concrete such as : <ul style="list-style-type: none"><li>■ Highways</li><li>■ Runways and taxiways</li><li>■ Aprons and hardstandings</li><li>■ Roof decks</li><li>■ Retaining walls</li></ul>
<b>Characteristics / Advantages</b>	Antisol® E provides the following beneficial properties to concrete surface. <ul style="list-style-type: none"><li>■ Reduces incidence of plastic cracking</li><li>■ Ensures achievement of desired strengths</li><li>■ Minimizes shrinkage</li><li>■ Reduces dusting</li><li>■ Forms a transparent coating on concrete</li></ul>
<b>Test</b>	
<b>Approval Standard</b>	ASTM C 309-89 Type 1 Class A
<b>Product Data</b>	
<b>Form</b>	
<b>Appearance / Colours</b>	White lump free liquid
<b>Packaging</b>	100 kg , 200 kg
<b>Storage</b>	
<b>Storage Conditions / Shelf-Life</b>	6 months from date of production if stored properly in unopened original packaging. Protect from frost.
<b>Technical Data</b>	
<b>Chemical Base</b>	Modified Paraffin Emulsion
<b>Relative Density</b>	~ 1.0 kg/l at 25°C



## System Information

### Application Details

<b>Consumption / Dosage</b>	0.15 to 0.20 kg/m <sup>2</sup> depending on wind, humidity and temperature. Actual dosage to be finalised on the basis of site trials.
<b>Application Method/ Tools</b>	Antisol® E curing membrane has been designed for spray application to the newly laid concrete once the surface water has evaporated. A thin film of Antisol® E is then applied to the whole surface using a suitable spray gun. STIR WELL BEFORE USE After application the area concerned must be protected from rain for at least 2 - 3 hours
<b>Notes on Application/Limitations</b>	Remaining Antisol® E films must be removed prior to application of any screed, plaster or coatings on the concrete surface.
<b>Cleaning of Tools</b>	Clean all tools and application equipment with petrol immediately after use.

### Value Base

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### Health and Safety Information

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

### Legal Notes

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Registered office: Sika India Pvt. Ltd.  
Commercial Complex II  
620, Diamond Harbour Road  
Kolkata, 700 034, India

Phone +91 33 2447 2448/2449  
Telefax +91 33 2397 8688  
ind.sika.com  
info.india@in.sika.com