Sikadur[®]-52 LP (IN), Component B

Revision Date 23.12.2019



1. PRODUCT AND COMPANY IDENTIFICATION

Manufacturer or supplier's details		
Type of product		liquid
Product code		10000014235
Product name	:	Sikadur [®] -52 LP (IN), Component B

Company	 Sika India Private Ltd. Unit 501-502, B- Wing, 5th floor Lotus Corporate Park Off Western Express Highway Goregaon East Mumbai 400 063
Telephone	: +9122 6270 4038
E-mail address	: ehs.india@in.sika.com
Emergency telephone num- ber	: +9122 6270 4038

2. HAZARDS IDENTIFICATION

Manufacture, Storage and Import of Hazardous Chemicals Rules 1989

Classification	
Flammable liquid GHS Classification	
Flammable liquids	: Category 4
Acute toxicity (Oral)	: Category 5
Acute toxicity (Inhalation)	: Category 4
Acute toxicity (Dermal)	: Category 5
Skin corrosion/irritation	: Sub-category 1B
Serious eye damage/eye irri- tation	: Category 1
Skin sensitisation	: Category 1
Short-term (acute) aquatic hazard	: Category 2
Long-term (chronic) aquatic hazard	: Category 3
GHS label elements	
Hazard pictograms	
Signal word	: Danger
	-

Sikadur[®]-52 LP (IN), Component B



Revision Date 23.12.2019 Hazard statements : H227 Combustible liquid. H303 + H313 May be harmful if swallowed or in contact with skin. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H332 Harmful if inhaled. H401 Toxic to aquatic life. H412 Harmful to aquatic life with long lasting effects. Precautionary statements : Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. **Response:** P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P312 Call a POISON CENTER/ doctor if you feel unwell. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. Storage: P403 Store in a well-ventilated place. P405 Store locked up. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (%)
Polyoxypropylenediamine	9046-10-0	>= 50 - < 70

Sikadur[®]-52 LP (IN), Component B



Revision Date 23.12.2019

Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8	>= 10 - < 20
Cashew, nutshell liq.	8007-24-7	>= 10 - < 20
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	>= 3 - < 5
2,2'-iminodiethylamine	111-40-0	>= 3 - < 5

4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Consult a physician.	
If inhaled	Show this safety data sheet to the doctor in attendance.Move to fresh air.Consult a physician after significant exposure.	
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficutly. 	11-
In case of eye contact	 Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plent of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing. 	
If swallowed	 Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Take victim immediately to hospital. 	
Most important symptoms and effects, both acute and delayed	 Health injuries may be delayed. corrosive effects sensitising effects Respiratory disorder Allergic reactions Headache Dermatitis See Section 11 for more detailed information on health effect and symptoms. May be harmful if swallowed or in contact with skin. May cause an allergic skin reaction. Causes serious eye damage. Harmful if inhaled. 	s
Notes to physician	Causes severe burns. : Treat symptomatically.	

5. FIREFIGHTING MEASURES

Suitable extinguishing media Unsuitable extinguishing media	: Carbon dioxide (CO2) : Water
	: No hazardous combustion products are known
Specific extinguishing meth- ods	: Standard procedure for chemical fires.

Sikadur[®]-52 LP (IN), Component B



Revision Date 23.12.2019

Special protective equipment : In the event of fire, wear self-contained breathing apparatus. for firefighters

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	: Use personal protective equipment. Deny access to unprotected persons.	
Environmental precautions	: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.	I
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.	

7. HANDLING AND STORAGE

Advice on protection against fire and explosion	: Normal measures for preventive fire protection.
Advice on safe handling	 Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the ap-
Conditions for safe storage	 billocating, eating and drinking should be prombted in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical products Store in original container. Keep in a well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
2,2'-iminodiethylamine	111-40-0	TWA	1 ppm	ACGIH

Personal protective equipment

Respiratory protection

: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that

Sikadur[®]-52 LP (IN), Component B



Revision Date 23.12.2019

Hand protection	 exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used. Chemical-resistant, impervious gloves complying with an ap- proved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec- essary.
Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	: Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.
Hygiene measures	 Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Colour Odour Odour Threshold	:	liquid light yellow No data available No data available
pH Melting point/range / Freezing point	:	Not applicable No data available
Boiling point/boiling range	:	No data available
Flash point	:	61 °C (142 °F) Method: closed cup
Evaporation rate	:	No data available
Flammability	:	No data available
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	0.01 hPa (0.01 mmHg)
Relative vapour density	:	No data available
Density	:	ca. 0.96 g/cm3 (20 °C (68 °F) ())
Solubility(ies) Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-	:	No data available

Sikadur[®]-52 LP (IN), Component B

Revision Date 23.12.2019



octanol/water Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity Viscosity, dynamic	: 17 mPa.s (30 °C)
Viscosity, kinematic	: 17.7 mm2/s (30 °C)
Explosive properties	: No data available
Molecular weight	: No data available

10. STABILITY AND REACTIVITY

Reactivity Chemical stability Possibility of hazardous reac- tions	 No dangerous reaction known under conditions of normal use. The product is chemically stable. Stable under recommended storage conditions.
Conditions to avoid Incompatible materials No decomposition if stored and	 No data available No data available applied as directed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

May be harmful if swallowed or in contact with skin. Harmful if inhaled.

Components:

Polyoxypropylenediamine: Acute oral toxicity	: LD50 Oral (Rat): 2,880 mg/kg
Amines, polyethylenepoly-, Acute oral toxicity	triethylenetetramine fraction: : LD50 Oral (Rat): 1,716 mg/kg
Acute dermal toxicity	: LD50 Dermal (Rabbit): 1,465 mg/kg
Cashew, nutshell liq.: Acute oral toxicity	: LD50 Oral (Rat): 500 mg/kg
Acute dermal toxicity	: LD50 Dermal (Rat): 2,000 mg/kg
2,4,6-tris(dimethylaminomet Acute oral toxicity	hyl)phenol: : LD50 Oral (Rat): 2,169 mg/kg
2,2'-iminodiethylamine: Acute oral toxicity	: LD50 Oral (Rat): 1,553 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 0.071 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	: LD50 Dermal (Rat): 1,045 mg/kg

Sikadur[®]-52 LP (IN), Component B





Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction. Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:	
Polyoxypropylenediamine: Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (algae)): 15 mg/l
	Exposure time: 72 h
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	: EC50 (Daphnia magna (Water flea)): 80 mg/l Exposure time: 48 h
2,4,6-tris(dimethylaminometh	nyl)phenol:
Toxicity to algae	: EC50 (Scenedesmus capricornutum (fresh water algae)): > 10 - 100 mg/l Exposure time: 72 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Sikadur[®]-52 LP (IN), Component B



Revision Date 23.12.2019

Additional ecological infor- : Harmful to aquatic life with long lasting effects. mation

13. DISPOSAL CONSIDERATIONS

Disposal methods		
Waste from residues	The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemi- cal or used container.	
Contaminated packaging	 Send to a licensed waste management company. Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum. 	

14. TRANSPORT INFORMATION

International Regulations

		-	-	_	~
υ	N	R		υ	Gi

UN number Proper shipping name Class Packing group Labels	:	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. 9 III 9
IATA-DGR UN/ID No. Proper shipping name Class Packing group Labels Packing instruction (cargo aircraft) Packing instruction (passen- ger aircraft)		9 III Miscellaneous 964
IMDG-Code UN number Proper shipping name Class Packing group Labels EmS Code Marine pollutant	::	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. 9 III 9 F-A, S-F no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

Sikadur[®]-52 LP (IN), Component B



Revision Date 23.12.2019

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

16. OTHER INFORMATION

Date format

: dd.mm.yyyy

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.