

# SAFETY DATA SHEET

## Sikadur®-330 (IN), Component B



Revision Date 05.08.2017

Print Date 19.09.2018

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikadur®-330 (IN), Component B  
Product code : 000000612231  
Type of product : liquid

#### Manufacturer or supplier's details

Company : Sika India Private Ltd.  
Unit 501-502, B- Wing, 5th floor  
Lotus Corporate Park  
Off Western Express Highway  
Goregaon East  
Mumbai 400 063

Telephone : +9122 6270 4038

E-mail address : ehs.india@in.sika.com

Emergency telephone number : +9122 6270 4038

### 2. HAZARDS IDENTIFICATION

#### Manufacture, Storage and Import of Hazardous Chemicals Rules 1989

##### Classification

Flammable liquid

##### GHS Classification

Flammable liquids : Category 4

Skin corrosion/irritation : Sub-category 1B

Serious eye damage/eye irritation : Category 1

Skin sensitisation : Category 1

Chronic aquatic toxicity : Category 2

##### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H227 Combustible liquid.  
H314 Causes severe skin burns and eye damage.

# SAFETY DATA SHEET

## Sikadur®-330 (IN), Component B



Revision Date 05.08.2017

Print Date 19.09.2018

H317 May cause an allergic skin reaction.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  
P391 Collect spillage.  
**Storage:**  
P403 Store in a well-ventilated place.  
P405 Store locked up.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

None known.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Hazardous components

Chemical name	CAS-No.	Concentration (%)
polyaminoamide adduct	157707-73-8	>= 30 - < 50
Quartz (SiO <sub>2</sub> )	14808-60-7	>= 20 - < 30
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8	>= 20 - < 25

## 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

# SAFETY DATA SHEET

## Sikadur®-330 (IN), Component B



Revision Date 05.08.2017

Print Date 19.09.2018

	<p>Consult a physician. Show this safety data sheet to the doctor in attendance.</p>
If inhaled	<p>: Move to fresh air. Consult a physician after significant exposure.</p>
In case of skin contact	<p>: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.</p>
In case of eye contact	<p>: Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.</p>
If swallowed	<p>: Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Take victim immediately to hospital.</p>
Most important symptoms and effects, both acute and delayed	<p>: Health injuries may be delayed. corrosive effects sensitising effects Allergic reactions Dermatitis See Section 11 for more detailed information on health effects and symptoms. May cause an allergic skin reaction. Causes serious eye damage. Causes severe burns.</p>
Notes to physician	<p>: Treat symptomatically.</p>

---

### 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Carbon dioxide (CO <sub>2</sub> )
Unsuitable extinguishing media	: Water
Specific hazards during fire-fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: No hazardous combustion products are known
Specific extinguishing methods	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

# SAFETY DATA SHEET

## Sikadur®-330 (IN), Component B



Revision Date 05.08.2017

Print Date 19.09.2018

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

---

### 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products

Conditions for safe storage : Store in original container.  
Keep in a well-ventilated place.  
Observe label precautions.  
Store in accordance with local regulations.

---

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

#### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.  
The filter class for the respirator must be suitable for the max-

# SAFETY DATA SHEET

## Sikadur®-330 (IN), Component B



Revision Date 05.08.2017

Print Date 19.09.2018

imum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

---

### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : paste
- Colour : black
- Odour : amine-like
- Odour Threshold : No data available
- pH : No data available
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : 62 °C (144 °F)  
Method: closed cup
- Evaporation rate : No data available
- Flammability : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : 0.01 hPa (0.01 mmHg)
- Relative vapour density : No data available

# SAFETY DATA SHEET

## Sikadur®-330 (IN), Component B



Revision Date 05.08.2017

Print Date 19.09.2018

Density	: 1.18 g/cm <sup>3</sup> (20 °C (68 °F) ())
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: 2,500 mPa.s (30 °C)
Viscosity, kinematic	: > 20.5 mm <sup>2</sup> /s (40 °C)
Explosive properties	: No data available
Molecular weight	: No data available

---

### 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: No data available
Incompatible materials	: No data available
No decomposition if stored and applied as directed.	

---

### 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Components:

#### **Amines, polyethylenepoly-, triethylenetetramine fraction:**

Acute oral toxicity : LD50 Oral (Rat): 1,716 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,465 mg/kg

#### **Skin corrosion/irritation**

Causes severe burns.

#### **Serious eye damage/eye irritation**

Causes serious eye damage.

# SAFETY DATA SHEET

## Sikadur®-330 (IN), Component B



Revision Date 05.08.2017

Print Date 19.09.2018

### Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

Not classified based on available information.

### STOT - repeated exposure

Not classified based on available information.

### Aspiration toxicity

Not classified based on available information.

---

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

No data available

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : Toxic to aquatic life with long lasting effects.

---

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

# SAFETY DATA SHEET

## Sikadur®-330 (IN), Component B



Revision Date 05.08.2017

Print Date 19.09.2018

### 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

UN number : UN 1760  
Proper shipping name : CORROSIVE LIQUID, N.O.S.  
Class : 8  
Packing group : III  
Labels : 8

##### IATA-DGR

UN/ID No. : UN 1760  
Proper shipping name : Corrosive liquid, n.o.s.  
Class : 8  
Packing group : III  
Labels : 8  
Packing instruction (cargo aircraft) : 856  
Packing instruction (passenger aircraft) : 852

##### IMDG-Code

UN number : UN 1760  
Proper shipping name : CORROSIVE LIQUID, N.O.S.  
Class : 8  
Packing group : III  
Labels : 8  
EmS Code : F-A, S-B  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### 15. REGULATORY INFORMATION

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

### 16. OTHER INFORMATION

Date format : dd.mm.yyyy

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.