

# PRODUCT DATA SHEET

## Sika® Antisol® A-4

### WATER DISPERSED, ACRYLIC COPOLYMER BASED CONCRETE CURING COMPOUND

#### DESCRIPTION

Sika® Antisol® A-4 is a water dispersed acrylic copolymer based curing compound. It is ready to use and simple to apply. Sika® Antisol® A-4 will form a thin film, covering the surface of the concrete to prevent premature water loss due to evaporation.

#### USES

Sika® Antisol® A-4 is sprayed on to newly laid concrete surfaces to form a thin film barrier against premature water loss, without disturbing the normal setting action. Sika® Antisol® A-4 is suitable where subsequent surface treatment with acrylic paints and polymer modified mortar or plaster etc. are required.

#### CHARACTERISTICS / ADVANTAGES

Sika® Antisol® A-4 provides the following beneficial properties to the concrete surfaces:

- Reduces incidence of plastic cracking
- Reduces shrinkage
- Reduces surface dusting
- Eliminates expensive methods of curing such as hessian-watering, etc.

#### APPROVALS / STANDARDS

ASTM C309, Type I, Class B

#### PRODUCT INFORMATION

<b>Chemical Base</b>	Water-dispersed, acrylic copolymer
<b>Packaging</b>	230kg
<b>Appearance / Colour</b>	Milky white liquid
<b>Shelf Life</b>	6 months from date of production if stored properly in unopened original packaging.
<b>Storage Conditions</b>	Store in dry condition at temperatures +10 to +40°C. Protect from frost and direct sun light.
<b>Density</b>	~ 1.01 kg/l @ 25°C

## APPLICATION INFORMATION

### Consumption

5 to 6.5 m<sup>2</sup> per liter depending on wind, humidity and temperature condition. Actual dosage to be finalised on the basis of site trials.

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY / PRE-TREATMENT

Clean concrete surface before application. Remove loose materials, dust and oil stains.

### APPLICATION

Spray application on newly laid concrete as soon as surface water evaporates. Roller and brush can be used for hardened concrete.

For vertical surfaces, apply immediately after removal of formwork.

After application, the area must be protected from rain for at least 2-3 hours.

## LIMITATIONS

Sika® Antisol® A-4 is transparent after curing.

Do not apply Sika® Antisol® A-4 on contaminated concrete surfaces (mould release agent, oil, stains, etc.) as this can lead to concrete stains and reduce the bond of subsequent coats

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Sika India Pvt. Ltd.

620, Diamond Harbour Road  
Commercial Complex II  
Kolkata - 700 034  
Tel : +91 33 24472448  
Fax : +91 33 23978688  
Mail : info.india@in.sika.com



### Product Data Sheet

Sika® Antisol® A-4  
December 2018, Version 01.01  
021405031000000127

SikaAntisolA-4-en-IN-(12-2018)-1-1.pdf