

PRODUCT DATA SHEET

Sika® Antisol® A

ALUMINIUM RESIN BASED CURING COMPOUND

DESCRIPTION

A curing compound based on aluminised synthetic resin for the prevention of premature water loss from concrete. It is in ready to use form and simple to apply. It has aluminium flakes for reflection of heat and thus providing extra cover for prevention of water loss.

USES

Sika® Antisol® A is sprayed on to newly laid concrete surfaces to form a thin film barrier against premature water loss. Without disturbance to the normal setting action the concrete is then allowed to cure and achieve maximum properties. Sika® Antisol® A is particularly useful in large areas of exposed concrete such as :

- Highways
- Runways and taxiways
- Aprons and hardstandings
- Roof decks
- Retaining walls
- Canals etc.

CHARACTERISTICS / ADVANTAGES

Sika® Antisol® A provides the following beneficial properties to concrete surfaces:

- Reduces incidence of plastic cracking
- Reduces shrinkage
- Reduces dusting
- Increases frost resistance
- Replaces labour intensive curing methods such as wet-Hessian, watering, etc.

APPROVALS / STANDARDS

ASTM C309 and BS 7542

PRODUCT INFORMATION

Chemical Base	Aluminized resin based liquid
Packaging	80Kg drum
Appearance / Colour	Aluminized liquid
Shelf Life	12 months from date of manufacturing when stored properly in unopened original packaging.
Storage Conditions	Keep in cool and dry place away from direct sunlight. Protect from frost.
Density	0.84 – 0.87 kg/l at 30°C

APPLICATION INFORMATION

Consumption

5–6.5 m² per litre depending on wind, humidity and temperature conditions.

APPLICATION INSTRUCTIONS

APPLICATION

Sika® Antisol® A is ready to use. Do not dilute. Stir well before use.

Sika® Antisol® A has been designed for spray application to the newly laid concrete once the surface water has evaporated. A thin layer of Antisol®-A is then applied to the whole surface using a hand operated spraygun. For large areas application can be done by power driven automatic equipment.

After application, the area must be protected from rain for at least 2–3 hours.

LIMITATIONS

Remaining Sika® Antisol® A films must be removed prior to application of any screed, plaster or coating on the concrete vertical surfaces.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika India Pvt. Ltd.

620, Diamond Harbour Road
Commercial Complex II
Kolkata - 700 034
Tel : +91 33 24472448
Fax : +91 33 23978688
Mail : info.india@in.sika.com



Product Data Sheet
Sika® Antisol® A
November 2018, Version 02.01
021405031000000031

SikaAntisolA-en-IN-(11-2018)-2-1.pdf