

## PRODUCT DATA SHEET

# SikaProof®-937 UVS

(formerly MSeal 937UVS)

### SINGLE-SIDED STICKY TAPE FOR SIKAPROOF®-730 UVS HDPE PRE-APPLIED WATERPROOFING SYSTEM

#### DESCRIPTION

SikaProof®-937 UVS is a white or light yellow single-sided sticky, HDPE self-adhesive tape. It is designed for use in underground waterproofing termination detailing along with SikaProof®-730 PA membrane system.

National Standard GB 27789-2011

#### USES

SikaProof®-937 UVS is used for long edge treatment or mending as part of the SikaProof®-730 PA membrane system.

SikaProof®-937 UVS is applied to waterproofing and damp-proofing engineering's for various underground building structures and basements.

#### CHARACTERISTICS / ADVANTAGES

The specially-made high density thermoplastic polyethylene (HDPE) film works as a waterproof base material. On one side the HDPE film is covered with macromolecule self-adhesive film and on the exposed surface the composite adhesive. The weather-resistant protective and insulating layer belongs to macromolecule self-adhesive film.

#### PRODUCT INFORMATION

<b>Packaging</b>	120mm x 50m x 0.3mm thickness one side sticky tape
<b>Shelf life</b>	12 months
<b>Storage conditions</b>	Stored properly in unopened, undamaged, original packaging in dry conditions and at temperatures between +5°C and +30°C.
<b>Tensile strength</b>	800 N/50mm
<b>Elongation at break</b>	500%
<b>Joint shear resistance</b>	5 N/mm (GB/T 328.23)
<b>Flexibility at low temperature</b>	-25°C, No crack
<b>Resistance to lateral water migration</b>	0.6MPa, No immigration

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

### APPLICATION

SikaProof®-937 UVS is part of the SikaProof®-730 PA membrane system, please refer to the relevant method statement.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**Sika India Pvt. Ltd.**  
620, Diamond Harbour Road  
Commercial Complex II  
Kolkata - 700 034  
West Bengal, India

**Contact:**  
Phone: +91 33 2447 2448  
Fax: +91 33 2397 8688  
info.india@in.sika.com  
www.sika.in



**Product Data Sheet**  
**SikaProof®-937 UVS**  
September 2024, Version 02.01  
02072000000002012

SikaProof-937UVS-en-IN-(09-2024)-2-1.pdf