

BUILDING TRUST

PRODUCT DATA SHEET

Sika® Cleaner-011

(formerly Sika®Cleaner PIN)

Solvent based Cleaner for non porous substrates

TYPICAL PRODUCT DATA (FURTHER VALUES SEE SAFETY DATA SHEET)

Chemical base	Solvent based Cleaner
Color	Colourless, clear liquid
Density	~ 0.79 kg/ lit (at 20°C)
Application temperature	min.+5°C; Max.+45°C
Application method	Wiping with lint-free paper towel
Flash point (CQP007-1 / ISO 13736)	ca. 12°C (54 °F) (Method: closed cup)
Shelf life (storage below 25°	C) 12 months ^A

CQP = Corporate Quality Procedure

A) stored in sealed container in a dry place at \leq 25 °C

DESCRIPTION

Sika®Cleaner-011 is a one-part solvent con- - Ready to use taining cleaner for non-porous substrates - Excellent cleaning properties

PRODUCT BENEFITS

- Easy to use
- Fast Process

AREAS OF APPLICATION

Sika®Cleaner-011 can be used to remove foreign matter and con-taminants, such as grease, oil, dust and dirt from the surface. Sika®Cleaner-011 is suitable for cleaning Glass surface, Aluminium surface, Painted surface, Appropriately prepared metallic and mineral components. Advice on specific applications will be given on request.

The above information is offered for general guidance only. Advice on specific applications will be given on request. This product is suitable for experienced professional users only. Test with actual substrates and conditions have to be performed to ensure adhesion and material compatibility.

Version 01.01 (12 - 2023), en_IN 014362000010023000

METHOD OF APPLICATION

Sika®Cleaner-011 can be used in application and surface temperature between 5°C and 45°C. Use only clean, white, lint-free paper towels. Wet the paper towel with solvent by pouring the liquid onto the cloth. Never dip the paper towel into the cleaner as it may contaminate it! Wipe the surface with the wetted paper towel. Use fresh paper towels regularly in order to retain the cleansing power.

If cleaned parts are not bonded subsequently cover them in order to prevent new contamination. If the time between cleaning and further processing is more than two hours, repeat the treatment as described above.

Tightly re-seal container immedi-ately after each use.

IMPORTANT NOTE

Compatibly with the actual substrate is to be verified prior the application. Discard any Sika®Cleaner-011 that loses its clear appearance (con-taminated). Advice on specific surface pre-treatment for various substrates is available from the Technical Service Department of Sika Industry.

Notes on Application / Limitations

Do not open until ready to use, and store in a sealed container after opening. Vapours should not be inhaled. Wear all appropriate PPE when using. Tightly re-seal container immediately after each use. Sika® Cleaner- 011 must be used within one month after opening the container. The correct cleaning of the surface improves the long term performance of a sealed joint.

FURTHER INFORMATION PACKAGING INFORMATION

Can	1 Liter HDPE
	Can

BASIS OF PRODUCT DATA

All technical data stated in this document are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

HEALTH AND SAFETY INFORMATION

For information and advice regarding transportation, handling, storage and disposal of chemical products, users shall refer to the actual Safety Data Sheets containing physical, ecological, toxicological and other safety-related data.

DISCLAIMER

The information, and in particular, the recommendations relating to the application and enduse of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika® Cleaner-011 Version 01.01 (12 - 2023), en_IN 014362000010023000



