

# SAFETY DATA SHEET

## Sikadur®-330 (IN), Component A



Revision Date 05.08.2017

Print Date 19.09.2018

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikadur®-330 (IN), Component A  
Product code : 000000612230  
Type of product : liquid

#### Manufacturer or supplier's details

Company : Sika India Private Ltd.  
Unit 501-502, B- Wing, 5th floor  
Lotus Corporate Park  
Off Western Express Highway  
Goregaon East  
Mumbai 400 063

Telephone : +9122 6270 4038

E-mail address : ehs.india@in.sika.com

Emergency telephone number : +9122 6270 4038

### 2. HAZARDS IDENTIFICATION

#### Manufacture, Storage and Import of Hazardous Chemicals Rules 1989

##### Classification

Flammable liquid

##### GHS Classification

Flammable liquids : Category 4  
Skin corrosion/irritation : Category 2  
Serious eye damage/eye irritation : Category 2A  
Skin sensitisation : Category 1  
Chronic aquatic toxicity : Category 2

##### GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H227 Combustible liquid.  
H315 Causes skin irritation.

# SAFETY DATA SHEET

## Sikadur®-330 (IN), Component A



Revision Date 05.08.2017

Print Date 19.09.2018

H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of water.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  
P391 Collect spillage.

**Storage:**

P403 Store in a well-ventilated place.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

None known.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Hazardous components

Chemical name	CAS-No.	Concentration (%)
reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700)	25068-38-6	>= 50 - < 70
Quartz (SiO <sub>2</sub> )	14808-60-7	>= 20 - < 30
Hydrocarbons, C9, aromatics	64742-95-6	>= 2.5 - < 10

### 4. FIRST AID MEASURES

General advice

: Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.

If inhaled

: Move to fresh air.

# SAFETY DATA SHEET

## Sikadur®-330 (IN), Component A



Revision Date 05.08.2017

Print Date 19.09.2018

---

	Consult a physician after significant exposure.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Clean mouth with water and drink afterwards plenty of water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.
Most important symptoms and effects, both acute and delayed	: irritant effects sensitising effects Allergic reactions Excessive lachrymation Dermatitis See Section 11 for more detailed information on health effects and symptoms. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.
Notes to physician	: Treat symptomatically.

---

### 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Carbon dioxide (CO <sub>2</sub> )
Unsuitable extinguishing media	: Water
Specific hazards during fire-fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: No hazardous combustion products are known
Specific extinguishing methods	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparatus.

---

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Deny access to unprotected persons.
---	---

# SAFETY DATA SHEET

## Sikadur®-330 (IN), Component A



Revision Date 05.08.2017

Print Date 19.09.2018

- Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

### 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
- Conditions for safe storage : Store in original container. Keep in a well-ventilated place. Observe label precautions. Store in accordance with local regulations.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrocarbons, C9, aromatics	64742-95-6	TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	ACGIH

#### Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

# SAFETY DATA SHEET

## Sikadur®-330 (IN), Component A



Revision Date 05.08.2017

Print Date 19.09.2018

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

---

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: paste
Colour	: light brown
Odour	: odourless
Odour Threshold	: No data available
pH	: No data available
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: 62 °C (144 °F) Method: closed cup
Evaporation rate	: No data available
Flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 0.001 hPa (0.001 mmHg)
Relative vapour density	: No data available
Density	: 1.37 g/cm <sup>3</sup> (20 °C (68 °F) ())
Solubility(ies) Water solubility	: insoluble

# SAFETY DATA SHEET

## Sikadur®-330 (IN), Component A



Revision Date 05.08.2017

Print Date 19.09.2018

Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: 5,400 mPa.s
Viscosity, kinematic	: > 20.5 mm <sup>2</sup> /s (40 °C)
Explosive properties	: No data available
Molecular weight	: No data available

---

### 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: No data available
Incompatible materials	: No data available
No decomposition if stored and applied as directed.	

---

### 11. TOXICOLOGICAL INFORMATION

#### **Acute toxicity**

Not classified based on available information.

#### **Components:**

**reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700):**

Acute oral toxicity	: LD50 Oral (Rat): > 5,000 mg/kg
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 20,000 mg/kg

#### **Hydrocarbons, C9, aromatics:**

Acute oral toxicity	: LD50 Oral (Rat): > 2,000 mg/kg
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 2,000 mg/kg

#### **Skin corrosion/irritation**

Causes skin irritation.

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

# SAFETY DATA SHEET

## Sikadur®-330 (IN), Component A



Revision Date 05.08.2017

Print Date 19.09.2018

### Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

Not classified based on available information.

### STOT - repeated exposure

Not classified based on available information.

### Aspiration toxicity

Not classified based on available information.

---

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

**reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight  $\leq$  700):**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l  
aquatic invertebrates Exposure time: 48 h

#### **Hydrocarbons, C9, aromatics:**

Toxicity to algae : (Pseudokirchneriella subcapitata (green algae)): 2.6 - 2.9 mg/l  
Exposure time: 72 h

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : Toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

## Sikadur®-330 (IN), Component A



Revision Date 05.08.2017

Print Date 19.09.2018

---

### 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

### 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

- UN number : UN 3082  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
Class : 9  
Packing group : III  
Labels : 9

##### IATA-DGR

- UN/ID No. : UN 3082  
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.  
Class : 9  
Packing group : III  
Labels : 9  
Packing instruction (cargo aircraft) : 964  
Packing instruction (passenger aircraft) : 964

##### IMDG-Code

- UN number : UN 3082  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
Class : 9  
Packing group : III  
Labels : 9  
EmS Code : F-A, S-F  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.



# SAFETY DATA SHEET

## Sikadur®-330 (IN), Component A



Revision Date 05.08.2017

Print Date 19.09.2018

---

### 15. REGULATORY INFORMATION

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

---

### 16. OTHER INFORMATION

Date format : dd.mm.yyyy

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.