



BUILDING TRUST



PRODUCT DATA SHEET

Sikafloor® Colour Component

Colour paste for specific Sikafloor® epoxy systems (Formerly Pigment Paste EP TL / Pigment Paste EP UL)

DESCRIPTION

Sikafloor® Colour Component is the fourth component of specific Sikafloor® epoxy products for self-smoothing underlayment and topping.

USES

Sikafloor® Colour Component is designed to provide colour to the self-smoothing topping Sikafloor®-295 and self-smoothing underlayment Sikafloor®-296.

CHARACTERISTICS / ADVANTAGES

- In combination with the neutral part A, it provides great flexibility to the contractor's job start-up and stock keeping
- Provides good chemical and mechanical resistance
- Easy to mix and very good dispersion into the mix
- Pre-batched for corresponding products
- Solvent free, low odour
- Does not support growth of bacteria and fungus
- Wide range of ~RAL colours (consult Sika® representative)

PRODUCT INFORMATION

Composition	Epoxy with selected pigments	
Packaging	Pre-batched for Sikafloor®-295	0.5 kg container
	Pre-batched for Sikafloor®-296	0.2 kg container
Shelf life	12 months from date of production	
Storage conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +10 °C and +30 °C.	
Appearance and colour	Pasty liquid / Various colours Sikafloor® Colour Component is available separately in a number of colour shades. Please consult with Sika representative for more details.	

Important: Applied colours selected from colour charts will be approximate.

Important: Colour deviations may occur due to filling with quartz sand.

Important: For colour matching, apply colour sample and confirm selected colour under real lighting conditions.

Important: When product is exposed to direct UV exposure (sun, lamp, skylight, etc.), there may be some discolouration and colour variation, this has no influence on the function and performance of the floor finish. Use of clear UV resistant top coat may not prevent discoloration of underlying coatings.

Important: Do not use external pigment pastes with Sikafloor® coatings, this might change the final performance of respective Sikafloor® coatings.

SYSTEM INFORMATION

System structure	System	Product	Colour component
	Self-smoothing topping	Sikafloor®-295	Sikafloor® Colour Component, 0.5 kg
	Self-smoothing under-layer	Sikafloor®-296	Sikafloor® Colour Component, 0.2 kg

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER INFORMATION

Product Data Sheet of Sikafloor®-295
Product Data Sheet of Sikafloor®-296

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

MIXING

1. Prior to mixing all parts, mix separately Part A (neutral resin) using a low speed single paddle electric stirrer (300–400 rpm).
2. Pre-mix Part A and Sikafloor® Colour Component prior to next mixing steps, preferably one day prior to the application.

Note: For full process of mixing, refer to the Product Data Sheet of product being applied.

Important: Maintain equal mixing time to avoid colour difference.

Important: Mix full quantity of pre-batched Sikafloor® Colour Component to the Part A (neutral resin) of product being applied.

Important: Do not keep the lid open of the container for longer time.

Important: Do not mix Sikafloor® Colour Component with Sikafloor® products not specified in this Product Data Sheet.

Apurva India Pvt. Ltd.
New Udyog Mandir No. 2,
Office No. 203, 2nd Floor,
7-C, Pitamber Lane, Mahim (West)
Mumbai - 400 016
Maharashtra, India

Contact:
Phone: +91 22 6270 4038
info.india@in.sika.com
www.apurvaindia.in
www.sika.in

APPLICATION

Please refer to the corresponding Product Data Sheet of the product being applied.

CLEANING OF EQUIPMENT

Clean all tools and application equipment with Thinner C or suitable solvent immediately after use. Hardened / cured material can only be mechanically removed.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.