

## PRODUCT DATA SHEET

# Sarnabar<sup>®</sup>

### Fastening Profile for Sarnabar<sup>®</sup> System and Perimeter Fastening

#### DESCRIPTION


Folded galvanized steel fastening profile for the mechanical fastening of roof waterproofing membranes.

#### USES

For the mechanical fastening of roof waterproofing membranes to roofing structures and perimeter fastening in combination with Sarnafast<sup>®</sup> SF-4.8, Sarnafast<sup>®</sup> SBF-6.0 and Sarnabar<sup>®</sup> Tube SBT-20.

#### CHARACTERISTICS / ADVANTAGES

- Resistance to mechanical impact
- Resistant to most common environmental influences



#### APPROVALS / STANDARDS

- European Technical Approval ETA-23/0859
- FM Approval Standard 4470

#### PRODUCT INFORMATION

<b>Chemical base</b>	Hot-dip coated steel FVZS250GD + AZ150BC, according to DIN EN 10346 and DIN EN 10143, WN 1.0242 coated steel.
<b>Packaging</b>	Refer to current price list for packaging variations.
<b>Appearance / Colour</b>	Surface: _____ smooth
<b>Shelf life</b>	5 years from date of production.
<b>Storage conditions</b>	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions. Always refer to packaging.

## Dimensions

Width:	30 mm
Height:	7 mm
Thickness:	1.5 mm
Mass per area:	0.7 kg/m <sup>2</sup>

## TECHNICAL INFORMATION

### Corrosion resistance

Resistance 15 cycles Kesternich test according to:  
• EAD 030351-00-0402, A2.4

## APPLICATION INFORMATION

### Ambient air temperature

- 20 °C min. / + 60 °C max.

### Substrate temperature

- 30 °C min. / + 60 °C max.

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## IMPORTANT CONSIDERATIONS

- Installation work must only be carried out by Sika® trained and approved contractors, experienced in this type of application.
- The use of Sarnabar® Fastening Profile is limited to geographical locations with average monthly minimum temperatures of - 50 °C. Permanent ambient temperature during use is limited to + 50 °C.

## ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w).

### Sika India Pvt. Ltd.

620, Diamond Harbour Road  
Commercial Complex II  
Kolkata - 700 034  
West Bengal, India

### Contact:

Phone: +91 33 2447 2448  
Fax: +91 33 2397 8688  
info.india@in.sika.com  
www.sika.in



### Product Data Sheet

Sarnabar®

April 2026, Version 02.01  
02094505110000004

## APPLICATION INSTRUCTIONS

### APPLICATION

Sarnabar® Fastening Profile must be installed in accordance with Sika application manual and installations instructions.

### LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

### LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sarnabar-en-IN-(04-2026)-2-1.pdf