

PRODUCT DATA SHEET

Sika® Antisol A1 (IN)

Concrete curing compound

DESCRIPTION

A curing compound based on aluminised synthetic resin for the prevention of premature water loss from concrete. It is in ready to use form and simple to apply.

USES

Sika® Antisol A1 (IN) is sprayed on to newly laid concrete surfaces to form a thin film barrier against premature water loss. Without disturbance to the normal setting action the concrete is then allowed to cure and achieve maximum properties.

Sika® Antisol A1 (IN) is particularly useful in large areas of exposed concrete such as :

- Highways
- PQC roads
- Runways and taxiways
- Aprons and hard standings
- Roof decks
- Retaining walls
- Canals etc.

CHARACTERISTICS / ADVANTAGES

Sika® Antisol A1 (IN) provides the following beneficial properties to concrete surfaces:

- Reduces incidence plastic cracking
- Ensures achievement of desired strength
- Minimises shrinkage
- Reduces dusting
- Increases frost resistance
- Alleviates other costly methods such as hessian-watering, etc

PRODUCT INFORMATION

Chemical base	Aluminum and synthetic resin based
Packaging	210Liters drums
Shelf life	6 months from date of manufacturing when stored properly in unopened original packaging.
Storage conditions	Store in dry conditions at temperatures between +10°C and +40°C. Keep in cool and dry place away from direct sunlight. Protect from frost.
Appearance / Colour	Aluminized thin liquid
Density	0.92 ~ 0.96 kg/l at 30°C

APPLICATION INFORMATION

Consumption

5-6 m² per litre, depending on wind, humidity and temperature. Actual dosage to be finalised on the basis of site trials. Spreading of this product depends on machine types, application method etc. Trials with the available equipments, machine, must be done prior to its actual use.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

Remaining Sika® Antisol A1 (IN) films must be removed prior to application of any screed, plaster or coating on the concrete surface.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

APPLICATION METHOD / TOOLS

Sika® Antisol A1 (IN) has been designed for spray application to the newly laid concrete once the surface water has evaporated. A thin layer of Sika® Antisol A1 (IN) is then applied to the whole surface using a hand operated spray gun. For large areas application can be done by power driven automatic equipment. Stir well before use. After application the area concerned must be protected from rain for at least 2-3 hours.

MAINTENANCE

CLEANING

Clean all tools and application equipment with petrol immediately after use.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika India Pvt. Ltd.

620, Diamond Harbour Road
Commercial Complex II
Kolkata - 700 034
West Bengal, India

Contact:

Phone: +91 33 2447 2448
Fax: +91 33 2397 8688
info.india@in.sika.com
www.sika.in



Product Data Sheet

Sika® Antisol A1 (IN)
November 2022, Version 01.01
021405031000000159

SikaAntisolA1IN-en-IN-(11-2022)-1-1.pdf