

PRODUCT DATA SHEET

Sikafloor® DecoFlakes

COLORED THIN LAMELLA OR FLAKES

DESCRIPTION

Flakes or lamellas of bright colors and defined sizes that placed on a colored resin like Sikafloor 264 and sealed with a translucent resin Sikafloor 169 or similar serves to realize decorative floors of great variety with a good chemical resistance and mechanical.

USES

The system of decorative floors with Sikafloor® Deco-Flakes, are used in:

- Offices / Cafes / Restaurants / Commercial Premises.
- Veterinary clinics / Waiting areas / Commercial premises.
- Warehouses / Exhibition Halls, etc.

CHARACTERISTICS / ADVANTAGES

- Bright colors
- Easy application
- Variety of designs
- Color combination
- Defined size

PRODUCT INFORMATION

Packaging	1 kg, 22.6 y 25 kg
Appearance / Colour	 Neutral Gray, White, Coffee and Black Size ¼"
Shelf Life	96 months from its date of production
Storage Conditions	Store in its original container in a dry and clean area

APPLICATION INSTRUCTIONS

The substrate must have a flat surface with good strength (minimum compressive strength approx. 250 kg/cm²), be healthy and dry (maximum substrate moisture 4%), free of loose parts, contamination of oils, residues of curators, grout or other foreign substances. Minimum tensile strength (pull-off): 15 kg/cm².

After a good surface preparation, depending on the porosity of the substrate, a Sikafloor 161 can be ap-

plied as a seal if necessary (Optional), then a resin with color of the Sikafloor type 264 is applied and then irrigation of Sikafloor® DecoFlakes, in the amount agreed or desired.

After drying, remove what has not adhered and all peaks and remove again the leftovers and apply a translucent resin of the type Sikafloor 169 (see technical sheets of the additional products). Consumption: From 120 gr to 800 gr/m² depending on the desired.

Product Data Sheet Sikafloor® DecoFlakes December 2018, Version 01.01 020816010040000009

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika India Pvt. Ltd.

620, Diamond Harbour Road Commercial Complex II Kolkata - 700 034 Tel : +91 33 24472448

Fax: +91 33 23978688 Mail: info.india@in.sika.com





Product Data Sheet Sikafloor® DecoFlakes December 2018, Version 01.01 020816010040000009



SikafloorDecoFlakes-en-IN-(12-2018)-1-1.pdf