



BUILDING TRUST



PRODUCT DATA SHEET

Sika® Quartz-03 IN

Quartz sand for broadcast in anti-skid flooring applications (Formerly AGGREGATE 40)

DESCRIPTION

Sika® Quartz-03 IN is graded, cleaned, dried quartz sand for broadcast and anti-skid flooring system.

USES

Sika® Quartz-03 IN has been specially developed for use in broadcast flooring systems based on epoxy or polyurethane resins.

CHARACTERISTICS / ADVANTAGES

- Compatible with Sikafloor® resin products
- Proper gradation ensuring uniform broadcast finish
- Enhances slip and abrasion resistance property
- Chemically inert

PRODUCT INFORMATION

Composition	Natural quartz sand
Packaging	25 kg bag
Shelf life	24 months from date of production
Storage conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. The packaging must be protected from moisture.
Appearance and colour	White quartz
Maximum grain size	~1.0 mm

APPLICATION INFORMATION

Consumption	Please refer to the following for guidance on recommended dosage for each system / product: <ul style="list-style-type: none">▪ System Data Sheet of Sikafloor® MultiDur EB▪ System Data Sheet of Sikafloor® MultiFlex for car parking decks
--------------------	---

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER INFORMATION

Refer to the following documents for detailed information on usage:

- Method Statement of Sikafloor® MultiDur EB
- Method Statement of Sikafloor® MultiFlex for car parking decks

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Apurva India Pvt. Ltd.
New Udyog Mandir No. 2,
Office No. 203, 2nd Floor,
7-C, Pitamber Lane, Mahim (West)
Mumbai - 400 016
Maharashtra, India

Contact:
Phone: +91 22 6270 4038
info.india@in.sika.com
www.apurvaindia.in
www.sika.in

Product Data Sheet
Sika® Quartz-03 IN
September 2022, Version 01.01
020816010010000122

SikaQuartz-03IN-en-INAPURVA-(09-2022)-1-1.pdf